

10/748343

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method for tracking a transmission status of one or more data elements to one or more routing devices, comprising:
  - providing a list including one or more routing devices and one or more data elements, wherein each data element includes a routing entry in a routing table;
  - processing the list to determine a data element of said one or more data elements to transmit to a routing device of one of the one or more routing devices; and
  - upon successfully transmitting the data element to the routing device, adjusting the list so that the list indicates that the routing device has received the transmitted data element.
2. (Currently Amended) The method of claim 1, wherein ~~the operation of providing~~ [[a]] the list includes forming a linked list between the data elements and the routing devices.
3. (Currently Amended) The method of claim 1, wherein ~~operation of providing~~ [[a]] the list further comprises:
  - providing a global version number;
  - providing a local version number associated with each said data element in the list; and
  - providing a local version number associated with each said routing device in the list.
4. (Currently Amended) The method of claim 3, wherein when [[a]] the data element is added to the list, the local version number associated with the data element is set to a value of an incremented global version number.
5. (Currently Amended) The method of claim 3, wherein the local version number associated with [[a]] the routing device in the list is set to an initial value of zero.

6. (Currently Amended) The method of claim 3, wherein the local version number associated with [[a]] the routing device in the list is set to an initial value of zero and is reset to the local version number of [[a]] the data element after the data element is successfully transmitted to the routing device.
7. (Currently Amended) The method of claim 3, wherein ~~the operation of providing~~ [[a]] the list further comprises:
- providing a pointer to a start of the list; and
  - providing a pointer to an end of the list.
8. (Currently Amended) The method of claim 7, further comprising:
- adding a data element to the end of the list; and
  - incrementing the global version number.
9. (Currently Amended) The method of claim 7, further comprising:
- adding a routing device to the beginning of the list.
10. (Currently Amended) The method of claim 3, wherein the operation of processing the list further comprises:
- locating [[a]] the routing device in the list which is nearest to a start of the list;
  - obtaining [[the]] a version number for the routing device; and
  - comparing the version number to the global version number to determine if the routing device should have [[a]] the data element transmitted to the routing device.
11. (Currently Amended) The method of claim 10, wherein the comparing operation determines that the routing device should have [[a]] the data element transmitted to the routing device if the version number of the routing device is not equal to the global version number.
12. (Currently Amended) The method of claim 1, wherein ~~operation of~~ adjusting the list further comprises:

repositioning the routing device within the list adjacent to the data element and closer to an end of the list than the data element.

13. (Currently Amended) The method of claim 3, wherein the operation of adjusting the list further comprises:

resetting the local version number of the routing device to be equal to the local version number of the transmitted data element.

14. (Currently Amended) A method for transmitting one or more data elements to one or more routing devices, comprising:

providing a list including one or more routing devices and one or more data elements, wherein each data element includes a routing entry in a routing table;

processing the list to determine a data element of said one or more data elements to transmit to a routing device of one of the one or more routing devices;

transmitting the data element to the routing device; and

adjusting the list to indicate that the routing device has received the transmitted data element.

15. (Currently Amended) The method of claim 14, wherein ~~operation of providing~~ operation of providing ~~the~~ the list includes forming a linked list between the data elements and the routing devices.

16. (Currently Amended) The method of claim 14, wherein the operation of providing ~~the~~ the list further comprises:

providing a global version number;

providing a local version number associated with each said data element in the list; and

providing a local version number associated with each routing device in the list.

17. (Currently Amended) The method of claim 16, wherein the local version number associated with ~~the~~ the data element in the list is set to a value of the global version number at a time when the data element was added to the list.

18. (Currently Amended) The method of claim 16, wherein the local version number associated with [[a]] the routing device in the list is set to an initial value of zero.
19. (Currently Amended) The method of claim 16, wherein the operation of processing the list further comprises:
- locating [[a]] the routing device in the list which is nearest to a start of the list;
  - obtaining the version number for the routing device; and
  - comparing the version number to the global version number to determine if the routing device should have a data element transmitted to the routing device.
20. (Currently Amended) The method of claim 19, wherein the comparing operation determines that the routing device should have [[a]] the data element transmitted to the routing device if the version number of the routing device is not equal to the global version number.
21. (Currently Amended) The method of claim 14, wherein the operation of adjusting the list further comprises:
- repositioning the routing device within the list adjacent to the data element and closer to an end of the list than the data element.
22. (Currently Amended) The method of claim 16, wherein the operation of adjusting the list further comprises:
- resetting the local version number of the routing device to be equal to the local version number of [[the]] a transmitted data element.
23. (Currently Amended) A router, comprising:
- a module for providing a list including one or more routing devices and one or more data elements, wherein each data element includes a routing entry in a routing table;

a module for processing the list to determine [[a]] the data element of said one or more data elements to transmit to a routing device of one of the one or more routing devices;

a module for transmitting the data element to the routing device; and

a module for adjusting the list so that the list indicates that the routing device has received the transmitted data element.